

# GE Sensing

## Features

- Waterproof sensing element and housing
- Compact transmitter with built-in sensor
- Bulk polymer resistance RH sensor
- Resistant to contamination
- Thermistor temperature measurement
- Temperature compensation

## Applications

- Greenhouses
- Textile mills
- Food processing
- Shipping containers

- Swimming pools
- Hospital suites

The EHRH Relative Humidity Transmitter is a waterproof RH sensing element and package which is ideally suited for monitoring relative humidity in high RH/harsh environment applications or where washdowns are required. The unit is designed for continuous monitoring of relative humidity and temperature and is available in  $\pm 2\%$  accuracy.

Both the sensor and electronics are contained in an epoxy-hardened enclosure designed for continuous service. A water-tight membrane filter is installed over the RH sensor for increased protection against high RH, contaminants and washdowns. The unit is designed to withstand 100% saturation.

The sensor incorporates a bulk polymer resistance element. The polymer is impervious to most contaminants and, since it is a bulk resistance device, surface contamination such as dust will not alter the accuracy of the readings.

The unit is provided with continuous temperature compensation which adjusts for temperature-induced change in the RH sensor output. The compensation provides high measurement accuracy over the entire operating range of the instrument.

---

# EHRH

## General Eastern Waterproof RH Transmitter

EHRH is a General Eastern product. General Eastern has joined other GE high-technology sensing businesses under a new name—GE Industrial, Sensing.



# EHRH Specifications

## Humidity

### Sensing Element

Resistance change of bulk polymer sensor

### Accuracy at 77°F (25°C)

±2% RH. 30 to 95% RH including hysteresis, linearity, and repeatability.

### Temperature Effect

Less than 0.11% per °F (0.06% per °C)

### Sensitivity

0.1% RH

### Repeatability

0.5% RH

### Linearity

See accuracy

### Hysteresis

Less than 1%

### Operating Range, Sensor & Electronics

0% to 100% RH, -20°F to 54°F (-4°C to 129°C)

### Maximum Air Velocity

10,000 ft/minimum (3,048 m/minimum)

### Output Ranges

4 to 20 mA current, two-wire, loop-powered for 0 to 100% RH (standard) into 0 to 900 Ω

## Adjustment

### Zero

±20%, non-interactive

### Span

±10%, non-interactive

### Long Term Stability

Less than 2% drift per year typical

## Power Supply

### Voltage

12 to 36 VDC

### Wiring Connection

Deutsch four-position waterproof connector (For front wiring only—flying leads for back wiring).

### Storage Temperature

-65°F to 70°F (-85°C to 158°C)

## Temperature

### Sensing Element

Thermistor, 10 kΩ at 77°F (25°C), two-wire measurement

### Accuracy at 77°F (25°C)

±0.5°F (±0.3°C). Also available with 100 (RTD with 4 mA to 20 mA analog output).

*Consult factory for further information.*



©2006 GE. All rights reserved.  
920-233A

All specifications are subject to change for product improvement without notice. GE® is a registered trademark of General Electric Co. Other company or product names mentioned in this document may be trademarks or registered trademarks of their respective companies, which are not affiliated with GE.

[www.gesensing.com](http://www.gesensing.com)